

# ComfortView™ Monitor Mounts



OVERVIEW | CAPABILITIES | FEATURES | SPECIFICATIONS

---

# OVERVIEW

The ComfortView™ monitor mounting system is part of every RedRick Technologies' workstation. Our solutions are specifically developed so that healthcare organizations can standardize their monitor configurations around today's large format diagnostic displays without risk of display sag or loss of adjustability over time.

We support displays for a variety of medical specialties, including:



Radiology



Cardiology



Mammography



Telemetry



Pathology


## Capabilities




of motorized monitor height adjustment



of adjustment towards and away from the viewer



of tilt/swivel in all directions



of rotation in either direction

- 200 lbs maximum monitor weight capacity
- Capabilities are based on one unit, but can be combined to support larger workstation setups with multiple monitor mounts
- VESA 75 and 100 compliant
- Adjustments to height and focal depth position can be made effortlessly to the entire monitor array at once

L2 Monitor Mount

L4 Monitor Mount



## Features

- Integrated cable management
- Integrated power distribution
- 15' data cables for a full range of adjustment and optimal cable routing
- 3, 4, or 6 USB 3.0 Connections



XL or dual display monitors such as Barco Fusion monitors account for two monitor spaces (as seen in the middle monitor above)



ComfortView™ L2 Monitor Mount



ComfortView™ L6 Monitor Mount



ComfortView™ L4S Monitor Mount



ComfortView™ L4 Monitor Mount

## L4S vs. L4

### L4S Mount

- Must contain a balanced load. Each outer monitor space must not exceed 12 lbs
- Cannot support over/under monitor configuration
- Contains one lifting column
- Maximum weight capacity of 85lbs

### L4 Mount

- Capacity to support a broader load/monitor configuration than the L4S
- Can support over/under monitor configuration
- Contains two lifting columns
- Maximum weight capacity of 200lbs

# SPECIFICATIONS

L2 L4S L4 L6

## Mounting Capabilities

Over/Under monitor mounting capable	✗	✗	✓	✓
Maximum Weight Capacity - lbs.	55	85	200	200
VESA compliant for 75mm and 100mm bolt pattern	✓	✓	✓	✓
Max Number of Monitor Spaces <small>*Please refer to monitor mount pictures</small>	2	4	4	6

## Adjustment Capabilities

Height Adjustment Range	12"	12"	12"	12"
User-defined height adjustment pre-sets (3 positions)	✓	✓	✓	✓
Horizontal (forward/back) adjustment of monitor set	16"	16"	16"	16"
Side/ side horizontal angle positioning	✓	✓	✓	✓
Tilt/ swivel in all directions, per individual monitor	15°	15°	15°	15°
Rotation in either direction, per individual monitor	90°	90°	90°	90°

## Accessories

Number of power bar outlets integrated into monitor mount	✗	4	6	6
Power transformer holder	○	✓	✓	✓
Cable management routing track for power and data cables	✓	✓	✓	✓
Excess cable storage for input devices	✗	✗	✓	✗
3, 4, or 6 port USB hub	○	✓	✓	✓

✓ Yes

○ Optional

✗ No



21624 Adelaide Road, Mount Brydges,  
Ontario, Canada, N0L 1W0  
T: 519.264.2400 | TF: 1.800.340.9511 | F: 519.264.2404  
[redricktechnologies.com](http://redricktechnologies.com)